

**PEACEMAKER® ClO<sub>2</sub> OXIDIZING/POLISHING STANDARD BLOWER  
 SPECIFICATIONS SUMMARY**

Blower Model	RPM	"WC	@	CFM	HP	Hz	PHASE	VOLTS	AMPS	kW	HEIGHT
<b>TOP MOUNTED</b>											
<b>AO-70</b>	3200	1.0	@	60	0.33	60	1	115	1.3	0.12	8.0"
<b>VBL 6</b>	3420	2.5	@	250	0.75	60	1	115/230	7.4/3.7	.55/.37	11.5"
<b>VBW 6</b>	3540	4.0	@	750	1.5	60	1	115/230	13.6/7.3	1.1	16.5"
<b>VBL 9</b>	3400	5.0	@	2200	3.4	60	3	230/460	7.8/4.5	2.4	19.5"
<b>FLOOR MOUNTED</b>											
<b>GI 20-224</b>	1880	9.0	@	3000	7.5	60	3	230/460	20.4/10.2	5.60	41-7/8"
<b>GI 20-264</b>	1700	9.0	@	5000	15.0	60	3	230/460	38.4/19.2	11.20	46-7/8"
<b>SWSI-18</b>	3230	11.7	@	7000	20.0	60	3	230/460	48.0/24.0	14.93	45-3/4"

NOTE: EXPLOSION PROOF motors are available if required by your local FIRE REGULATIONS. Individual and more detailed information on each blower model listed above can be found in our manuals.

**Limited Warranty:** Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user.