


**PEACEMAKER® H₂S CONVERTING/POLISHING STANDARD BLOWER
 SPECIFICATIONS SUMMARY**


BLOWER MODEL	RPM	WC @ CFM		VOLTS	Hz	PHASE	HP	AMPS	kW	HEIGHT	
TOP MOUNTED											
AO 70	3200	1.1	@ 60	115	60	1	0.033	1.3	0.13	8.0"	
VBL 6	3420	2.5	@ 250	115/230	60	1	0.75	7.4 / 3.7	0.55	11.5"	
VBW 6	3540	4.0	@ 750	115/230	60	1	1.5	13.6 / 7.3	1.1	16.5"	
VBW 9	3400	5.0	@ 2200	230/440	60	3	3.4-2.9	7.8 / 4.5	2.4	19.5"	

NOTE: EXPLOSION PROOF motors are available if required by your local FIRE REGULATIONS. Individual and more detailed information on each blower model listed above can be found in our manuals.

BLOWER CONFIGURATIONS



AO 70 Model



VBL/VBW Models

Limited Warranty:

Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user.