

PEACEMAKER® H₂S CONVERTING/POLISHING DRY AIR SCRUBBERS			
SIZING INFORMATION			
FLOW INFORMATION			
IMPORTANT – Flow information requested is <i>TO</i> , not from, the wet well to be scrubbed.			
1) Wet well size (Area to be Scrubbed)		FT ³	
2) CFM required		CFM	
3) Air Turnovers required		Times	
4) Average daily flow		MGD	
5) Peak hourly flow		MGD	
6) Pump rate capacity of all pumps combined		GPM	
7) Variable speed drive pumps (at the wet well to be scrubbed)	Yes	No	
8) Fresh Air Intake	Yes	No	
9) Gravity line enters wet well below liquid level	Yes	No	
LOAD INFORMATION			
1) Average atmospheric H ₂ S – Oda-Log			PPM
2) Peak atmospheric H ₂ S – Oda-Log			PPM
3) Average atmospheric H ₂ S – Grab			PPM
4) Peak atmospheric H ₂ S – Grab			PPM
FAN/POWER INFORMATION			
CFM must exceed the cubic foot displacement of peak flow and/or pump rates to wet well or other enclosed space being scrubbed. Please check below all power that is available.			
<input type="checkbox"/> 110/115V, 60 Hz, 1 Phase <input type="checkbox"/> 220/230, 60 Hz, 3 Phase <input type="checkbox"/> 440/460, 60 Hz, 3 Phase			
<p>For: _____</p> <p>Date: _____</p> <p>Phone: _____</p> <p>Fax: _____</p> <p>Email: _____</p>			

Limited Warranty:

Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product “as is” and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user.