

PEACEMAKER® OXIDIZING/POLISHING FAN SPECIFICATIONS SUMMARY

BLOWER MODEL	RPM	"WC	@	CFM	HP	Hz	PHASE	VOLTS	AMPS	Kw	HEIGHT
TOP MOUNTED (Effluent Fan)											
AO-70	3,200	1.1	@	60	0.33	60	1	115	1.3	0.12	8.0"
CBL 6	3,420	2.5	@	250	0.75	60	1	115/230	7.4/3.7	.55/.37	11.5"
CBW 6	3,540	3.2	@	750	1.5	60	1	115/230	13.6/7.3	1.1	16"
CBW 9	3,450	4.0	@	1,800	3	60	3	230/460	9.5/5	2.2	15"
FLOOR MOUNTED (Influent Fan)											
Chicago 2750	3,500	6.3	@	2,750	5	60	3	230/460	11.6/5.0	3.7	28.5"
Chicago 4250	1,760	4.8	@	4,250	7.5	60	3	230/460	19/9.5	5.6	28.5"
Chicago 6000	1,760	5.4	@	6,000	10	60	3	230/460	24.4	7.5	28.5"
Chicago 9000	1,760	6.1	@	9,000	15	60	3	230/460	36.2/18.1	11.2	28.5"

NOTE: EXPLOSION PROOF motors are available if required by your local FIRE REGULATIONS. Individual and more detailed information on each blower model listed above can be found in our manuals.

Limited Warranty: Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user.